



AGmetal TecnoLamp

LUMINARIA HAKAN 60W - 90W -150W



PRODUCT SPECIFICATIONS			
Model No.:	SW-SL407-W120-X, X can be S and M, S=SOSEN driver, M=Mean Well driver		
Power:	120W		
Input:	AC100-277V, 50/60Hz, 0.55A(at 220v); 347V/480V AC for option		
PF:	> 0.97		
IP Grade:	IP66		
THD:	10% (at 230v, 50Hz)		
Surge protection:	L/N-PE: 10KV, L-N: 6KV; /20KV are for option		
TECHNICAL CHARACTERISTICS			
Color:	Warm White	Natural White	Cool White
Color Temperature:	2700-3000K	4000K / 5000K	5700K / 6500K
CRI:	>70Ra	>70Ra	>70Ra
Light Efficiency:	130-140lm/w		
View angle:	Type 2, Type 3, Type 4, 60° , 90°		
CONFIGURATIONS			
LED chip:	3030 SMD LED(Lumileds)		
Heat sinks:	Aluminum		
Body color:	Grey		
OTHERS			
Operating Temperature:	-35°C - 50°C		
Operating Humidity:	10% - 90% RH		
Storage Temperature:	-35°C to 60°C		
Net W./Gross W.:	7.7KGS/8.7KGS		
Packing size:	75*38*20cm		
Warranty:	5 years		
Certificates:	CE, RoHS, IP66, IK08, TM21, LM79, LM80		

Carcasa de aluminio inyectado a alta presión con superficie autolimpiable de polvo y agua.

Base fotocelda NEMA 7

Sistema anti intrusión, que corta la energía eléctrica cuando se abre la tapa.

Brazo o acople luminaria a poste regulable +25° o -15°

Terminal de conexión y desconexión de fácil uso.

Protector SPD 10KV/20KV

Acceso a compartimiento eléctrico sin herramientas
Fácil retiro de equipamiento del sistema eléctrico para mantenimiento

Apertura de la luminaria sin uso de herramientas